


# Sundance Spas 980 Odessa™

## Specifications


<p><b>Dimensions:</b>..... 89" x 89" x 34" (226 cm x 226 cm x 86.4 cm)</p> <p><b>Seating Capacity:</b> ..... 6-7 Adults</p> <p><b>Dry Weight:</b>..... 813 lbs (369 kg)</p> <p><b>Filled Weight (Spa Volume):</b>..... 4,658 lbs (2,113 kg)</p> <p><b>Filled Weight (Average Fill):</b>..... 3,657 lbs (1,659 kg)</p> <p><b>Water Capacity (Spa Volume):</b>..... 461 US Gal (1,745 Liters)</p> <p><b>Water Capacity (Average Fill):</b>..... 341 US Gal (1,291 Liters)</p> <p><b>Controls:</b>..... 980 iTouch™ Glass Interface LCD Control, Displays Temperature, Time, Cycles and Jet/Air System Control. Offers Customizing of Filtration Cycles, Lighting, Water Temperature Setting and other features</p> <p><b>Water Delivery:</b> ..... 2 TheraMax High-Flow Pumps and 8-Hour Dynamic Flow Circulation System</p> <p><b>Pump 1:</b> ..... North America (60 Hz): 1-Speed/2.5 HP Continuous, 11.3A Max., 56 Frame <b>Export (50 Hz): 1-Speed/2.0 HP Continuous, 7A Max.</b></p> <p><b>Pump 2:</b> ..... North America (60 Hz): 1-Speed/2.5 HP Continuous, 11.3A Max., 56 Frame <b>Export (50 Hz): 1-Speed/2.0 HP Continuous, 7A Max.</b></p> <p><b>Pump 3:</b> ..... High-Output Dynamic Flow, 8-Hour Filter/Circulation Pump (35 gpm) Programmable for Daily Start Time and Duration</p> <p><b>Total Hydrojets:</b> ..... <b>37</b></p> <p><b>Seat A Jets:</b> ..... 2 Fluidix Nex, 4 Fluidix Reflex</p> <p><b>Seat B Jets:</b> ..... 2 Fluidix Reflex</p> <p><b>Seat C Jets:</b> ..... 2 Fluidix Nex, 12 Fluidix-ST, 2 Pulsator, 2 Accu-Pressure</p> <p><b>Seat D Jets:</b> ..... 1 Vortex</p> <p><b>Seat E Jets:</b> ..... 1 Vortex, 2 Fluidix Intelli-Jet</p> <p><b>Seat F Jets:</b> ..... 1 Vortex</p> <p><b>Seat G Jets:</b> ..... 2 Fluidix Nex, 2 Vortex</p> <p><b>Footwell Jets (H):</b>..... 2 Vortex</p> <p><b>Air Blower:</b> ..... High-efficiency, 1-Speed</p> <p><b>Aromatherapy Delivery:</b>..... 10 Silent Air® Injector Jets with Quiet High Speed Air Pump</p> <p><b>Air Controls/Massage Selectors:</b> ..... 4/2</p> <p><b>Filter:</b>..... MicroClean® Ultra Filtration System, 130 ft² (2 interlocking cartridge filters)</p> <p><b>Water Treatment:</b> ..... Automatic Brominator and Dynamic Flow Circulation System; Factory installed CLEARRAY® Water Purification System</p> <p><b>Water Treatment (Optional):</b> ..... Factory installed CLEARRAY PRO<sub>3</sub>TECT</p> <p><b>Lighting:</b> ..... Multicolored LED Lighting System (1 Waterfall, 1 Footwell), Exterior Corner Lights, Seat Accent Lights</p> <p><b>Synthetic Cabinet:</b> ..... Available in Coastal, Mahogany</p> <p><b>Shell Colors:</b> ..... Platinum, Celestite (Gypsum), Sahara, Oyster (Opal), Copper Sand, Monaco, Midnight, Caribbean Surf, Sandstone, Porcelain <b>Export: All North American Colors</b></p> <p><b>Headrests:</b>..... 4</p> <p><b>Heater:</b> ..... Low Flow 5.5 kW With Titanium Element <b>Export (50 Hz): Low Flow 2.7 kW with Titanium Element</b></p> <p><b>Electrical Requirements:</b> ..... North America (60 Hz): 240 VAC@40A/50A or 60A; <b>Export (50 Hz): 230-240 VAC@1x20A, 1x16A/1x20A, 3x16A (see manual for more configurations); or Suitable Rated Circuit Breaker To Comply With Local Electrical Regulations. Certain Countries May Require 2 Power Inputs; Two GFCI/RCD Breakers are Required For This Configuration.</b></p> <p><b>Limited Warranty*:</b>..... North America (60 Hz): 10 Years Shell, 7 Years Shell Surface, 5 Years Plumbing Component Leaks, 5 Years Equipment and Controls, 5 Years Cabinet, 5 Years Jets, 2 Years Lights, 1 Year Stereo <b>Export (50 Hz): 10 Years Shell, 7 Years Shell Surface, 5 Years Plumbing Component Leaks, 5 Years Equipment and Controls, 5 Years Cabinet, 5 Years Jets, 2 Years Lights, 2 Years Stereo</b></p> <p><b>Waterfall Feature:</b> ..... Adjustable Flow Rate; Colored Lighting</p> <p><b>Audio System (Optional):</b> ..... Factory Installed BLUEWAVE® 2.0 Wireless Spa Stereo System with Auxiliary 3.5 mm headphone jack connection, Bluetooth® compatible, 4 premium speakers and a powered subwoofer</p> <p><b>Special Features:</b>..... Factory Installed SmartTub™ module</p>	
--	---

\*(See Warranty Document for Specific Details)

Dimensions/Specifications Subject To Change Without Notice

# Sundance Spas 980 Odessa

## Operation/Seat Depths



- (A)** Air Control - Activates Seat A Jets (2 Fluidix Nex, 4 Fluidix Reflex) and Seat B Jets (2 Fluidix Reflex)
- (B)** Massage Selector [Pump 2] - Adjusts Massage Level Between Seat A Jets + Seat B Jets and Seat C Jets
- (C)** Air Control - Activates Seat C Jets (2 Fluidix Nex, 12 Fluidix ST, 2 Pulsators, 2 Accu-Pressure)
- (D)** Waterfall Selector [8-Hour Circ. Pump] - Controls Waterfall Output
- (E)** Air Control - Activates Seat E Jets (1 Vortex, 2 Fluidix Intelli-Jet) and Seat D Jets (1 Vortex)
- (F)** Massage Selector [Pump 1] - Adjusts Massage Level Between the Seat E Jets and Seat G Jets
- (G)** Air Control - Activates Seat F (1 Vortex), Seat G (2 Fluidix Nex, 2 Vortex and Footwell Jets (2 Vortex)
- (H)** SunScents Dispenser

- Jets Pump 1: Seat D (1 Vortex), Seat F (1 Vortex) and Footwell Jets (2 Vortex) are always on when this pump is running
- Jets Pump 2: Seat C (2 Accu-Pressure Jets are always on when this pump is running

### 37 Total Jets



Accu-Pressure Jets (2)



Pulsator Jets (2)



Fluidix Nex Jets (6)



Fluidix-ST Jets (12)



Fluidix Reflex Jets (6)



Fluidix Intelli-Jet (2)



Vortex Jets (7)

Spa Operation Subject To Change Without Notice

## SEAT DEPTHS

**A = 28.13" (71.45 cm)**

**B = 21.00" (53.34 cm)**

**C = 26.50" (67.31 cm)**

**D = 20.75" (52.71 cm)**

**E = 24.50" (62.23 cm)**

**F = 20.25" (51.44 cm)**

**G = 21.88" (55.58 cm)**

**H = 17.13" (43.51 cm)**

**I = 29.13" (73.99 cm)**




Listed dimensions represent distance from top of acrylic to lowest point in seat. **Tolerance  $\pm 0.5"$  (1.27 cm).**




Dimensions/Specifications Subject To Change Without Notice

# Sundance Spas 980 Odessa

## Portable Dimensions



**IMPORTANT! Always measure each hot tub for exact dimensions BEFORE designing its foundational support and/or decking.**



**Dimensions/specifications subject to change without notice. Tolerance: ± 0.5" (1.27 cm)**

Dimensions/Specifications Subject To Change Without Notice

Denne modellen kan kobles med 1-fas 230V C-sikring (treg) og 3-fas (400 volt TN-nett - se egne linjer)

**980-serien:**

<b>Odessa:</b> For å få mest mulig glede av badet anbefaler vi høyeste kurs for optimal drift.				
	<b>Type varmeelement</b>	<b>Alternativ tilkobling</b>	<b>Funksjon</b>	<b>Kretskortinnstillinger</b>
Odessa	5,5 kW	3-fas (400 volt TN-nett) 25 amp	Varmeelement og pumper kan brukes samtidig	Se brukermanual.
Odessa	5,5 kW	40 amp eller 20 + 25 amp	Varmeelement og pumper kan brukes samtidig	Se brukermanual.
Odessa	5,5 kW	25 amp	Alle pumper kan brukes samtidig. Varmeelementet slår seg automatisk av når pumpene startes.	Se brukermanual.
Odessa	2,7 kW	3-fas (400 volt TN-nett) 16 amp	Varmeelement og pumper kan brukes samtidig	Se brukermanual.
Odessa	2,7 kW	32 amp eller 16 + 20 amp	Varmeelement og pumper kan brukes samtidig	Se brukermanual.
Odessa	2,7 kW	20 amp	Alle pumper kan brukes samtidig. Varmeelementet slår seg automatisk av når pumpene startes.	Se brukermanual.